

Structure of message: Auction - auction request status (auct.str.001.01)

Description:

Auction - auction request status

Structure:

No.	Or	< XML Tag >	Name	Multiplicity	Type
0		KDPWDocument	KDPW_CCP system message	[1..1]	KDPWDocument
0.1		auct.str.001.01	Auction - auction request status	[1..1]	auct.str.001.01
1		GnlInf	General information	[1..1]	GeneralInformation
1.1		SndrMsgRef	Sender message reference	[1..1]	Max16Text
1.2		FuncOfMsg	Function of message	[1..1]	FunctionOfMessage
1.3		CreDtTm	Creation date and time	[0..1]	DateAndDateTimeChoice
1.3.1	{ or	Dt	Date	[1..1]	ISODate
1.3.2	or }	DtTm	Date and time	[1..1]	ISODateTime
1.4		Lnk	Linkages	[0..1]	Linkages
1.4.1		RltdRef	Related reference	[0..1]	Max16Text
2		Sts	Status	[1..1]	Status
2.1		StsCd	Status code	[1..1]	Code4Text
2.2		Rsn	Reason	[0..1]	Reason
2.2.1		RsnCd	Reason code	[0..1]	Code4Text
2.2.2		RsnTxt	Reason description	[0..1]	Max140Text

Message component elements:

KDPWDocument- KDPW_CCP system message (element)	
Description	KDPW_CCP system message
Type	KDPWDocument
Source	<xs:element name="KDPWDocument" type="KDPWDocument" />
Code4Text- Qualifier (simple type)	
Description	Qualifier, code
Type	Derivative of type: xs:string

Format	Min. length=4 Max. length=4
Source	<pre><xs:simpleType name="Code4Text" > <xs:restriction base="xs:string" > <xs:whiteSpace value="collapse" /> <xs:minLength value="4" /> <xs:maxLength value="4" /> </xs:restriction> </xs:simpleType></pre>
DateAndDateTimeChoice- Date and time (complex type)	
Description	Date and time
Component elements	Dt DtTm
Source	<pre><xs:complexType name="DateAndDateTimeChoice" > <xs:sequence > <xs:choice > <xs:element name="Dt" type="ISODate" /> <xs:element name="DtTm" type="ISODateTime" /> </xs:choice> </xs:sequence> </xs:complexType></pre>
DateAndDateTimeChoice/Dt- Date (element)	
Description	Date
Type	ISODate
Source	<pre><xs:element name="Dt" type="ISODate" /></pre>
DateAndDateTimeChoice/DtTm- Date and time (element)	
Description	Date and time
Type	ISODateTime
Source	<pre><xs:element name="DtTm" type="ISODateTime" /></pre>
FunctionOfMessage- Function of message (simple type)	
Description	Function of message
Type	Derivative of type: xs:string
Format	Code Description NEWMNew message
Source	<pre><xs:simpleType name="FunctionOfMessage" > <xs:restriction base="xs:string" > <xs:enumeration value="NEWM" /> </xs:restriction> </xs:simpleType></pre>
GeneralInformation- General information (complex type)	
Description	General information

Component elements	SndrMsgRef FuncOfMsg CreDtTm {0,1} Lnk {0,1}
Source	<pre><xs:complexType name="GeneralInformation" > <xs:sequence > <xs:element name="SndrMsgRef" type="Max16Text" /> <xs:element name="FuncOfMsg" type="FunctionOfMessage" /> <xs:element name="CreDtTm" type="DateAndDateTimeChoice" minOccurs="0" /> <xs:element name="Lnk" type="Linkages" minOccurs="0" /> </xs:sequence> </xs:complexType></pre>
GeneralInformation/SndrMsgRef- Sender message reference (element)	
Description	Sender message reference
Type	Max16Text
Source	<pre><xs:element name="SndrMsgRef" type="Max16Text" /></pre>
GeneralInformation/FuncOfMsg- Function of message (element)	
Description	Function of message
Type	FunctionOfMessage
Source	<pre><xs:element name="FuncOfMsg" type="FunctionOfMessage" /></pre>
GeneralInformation/CreDtTm- Creation date and time (element)	
Description	Creation date and time
Type	DateAndDateTimeChoice
Source	<pre><xs:element name="CreDtTm" type="DateAndDateTimeChoice" minOccurs="0" /></pre>
GeneralInformation/Lnk- Linkages (element)	
Description	Linkages
Type	Linkages
Source	<pre><xs:element name="Lnk" type="Linkages" minOccurs="0" /></pre>
ISODate- Data (simple type)	
Description	Date
Type	Derivative of type: xs:date
Format	
Source	<pre><xs:simpleType name="ISODate" > <xs:restriction base="xs:date" > </xs:restriction> </xs:simpleType></pre>
ISODateTime- Date and time (simple type)	
Description	Date and time
Type	Derivative of type: xs:dateTime

Format										
Source	<pre><xs:simpleType name="ISODateTime" > <xs:restriction base="xs:dateTime" > </xs:restriction> </xs:simpleType></pre>									
KDPWDocument- KDPW_CCP system message (complex type)										
Description	KDPW_CCP system message									
Attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Description</th> <th>Type</th> </tr> </thead> <tbody> <tr> <td>Sndr</td> <td>Sender</td> <td>KDPWMemberIdentifier</td> </tr> <tr> <td>Rcvr</td> <td>Receiver</td> <td>KDPWMemberIdentifier</td> </tr> </tbody> </table>	Name	Description	Type	Sndr	Sender	KDPWMemberIdentifier	Rcvr	Receiver	KDPWMemberIdentifier
Name	Description	Type								
Sndr	Sender	KDPWMemberIdentifier								
Rcvr	Receiver	KDPWMemberIdentifier								
Component elements	auct.str.001.01									
Source	<pre><xs:complexType name="KDPWDocument" > <xs:sequence > <xs:element name="auct.str.001.01" type="auct.str.001.01" /> </xs:sequence> < xs:attribute name="Sndr" type="KDPWMemberIdentifier" use="required" /> < xs:attribute name="Rcvr" type="KDPWMemberIdentifier" use="required" /> </xs:complexType></pre>									
KDPWDocument/auct.str.001.01- Auction - auction request status (element)										
Description	Auction - auction request status									
Type	auct.str.001.01									
Source	<pre><xs:element name="auct.str.001.01" type="auct.str.001.01" /></pre>									
KDPWMemberIdentifier- KDPW member identifier (simple type)										
Description	KDPW member identifier									
Type	Derivative of type: xs:string									
Format	Min. length=4 Max. length=4									
Source	<pre><xs:simpleType name="KDPWMemberIdentifier" > <xs:restriction base="xs:string" > <xs:whiteSpace value="collapse" /> <xs:minLength value="4" /> <xs:maxLength value="4" /> </xs:restriction> </xs:simpleType></pre>									
Linkages- Linkages (complex type)										
Description	Linkages									
Component elements	RltdRef {0,1}									
Source	<pre><xs:complexType name="Linkages" > <xs:sequence > <xs:element name="RltdRef" type="Max16Text" minOccurs="0" /> </xs:sequence > </xs:complexType></pre>									

	<pre></xs:sequence> </xs:complexType></pre>
Linkages/RltdRef- Related reference (element)	
Description	Related reference
Type	Max16Text
Source	<pre><xs:element name="RltdRef" type="Max16Text" minOccurs="0" /></pre>
Max4Text- Text (simple type)	
Description	Text, max. length 4 characters
Type	Derivative of type: xs:string
Format	Min. length=1 Max. length=4
Source	<pre><xs:simpleType name="Max4Text" > <xs:restriction base="xs:string" > <xs:whiteSpace value="collapse" /> <xs:minLength value="1" /> <xs:maxLength value="4" /> </xs:restriction> </xs:simpleType></pre>
Max16Text- Text (simple type)	
Description	Text, max. length 16 characters
Type	Derivative of type: xs:string
Format	Min. length=1 Max. length=16
Source	<pre><xs:simpleType name="Max16Text" > <xs:restriction base="xs:string" > <xs:minLength value="1" /> <xs:maxLength value="16" /> </xs:restriction> </xs:simpleType></pre>
Max140Text- Text (simple type)	
Description	Text, max. length 140 characters
Type	Derivative of type: xs:string
Format	Min. length=1 Max. length=140
Source	<pre><xs:simpleType name="Max140Text" > <xs:restriction base="xs:string" > <xs:minLength value="1" /> <xs:maxLength value="140" /> </xs:restriction> </xs:simpleType></pre>
Reason- Reason (complex type)	

Description	Reason
Component elements	RsnCd {0,1} RsnTxt {0,1}
Source	<pre><xs:complexType name="Reason" > <xs:sequence > <xs:element name="RsnCd" type="Code4Text" minOccurs="0" /> <xs:element name="RsnTxt" type="Max140Text" minOccurs="0" /> </xs:sequence> </xs:complexType></pre>
Reason/RsnCd- Reason code (element)	
Description	Reason code
Type	Code4Text
Source	<pre><xs:element name="RsnCd" type="Code4Text" minOccurs="0" /></pre>
Reason/RsnTxt- Reason description (element)	
Description	Reason description
Type	Max140Text
Source	<pre><xs:element name="RsnTxt" type="Max140Text" minOccurs="0" /></pre>
Status- Status (complex type)	
Description	Status
Component elements	StsCd Rsn {0,1}
Source	<pre><xs:complexType name="Status" > <xs:sequence > <xs:element name="StsCd" type="Code4Text" /> <xs:element name="Rsn" type="Reason" minOccurs="0" /> </xs:sequence> </xs:complexType></pre>
Status/StsCd- Status code (element)	
Description	Status code
Type	Code4Text
Source	<pre><xs:element name="StsCd" type="Code4Text" /></pre>
Status/Rsn- Reason (element)	
Description	Reason
Type	Reason
Source	<pre><xs:element name="Rsn" type="Reason" minOccurs="0" /></pre>
auct.str.001.01- Auction - auction request status (complex type)	
Description	Auction - auction request status
Component elements	GnlInf Sts

Source	<pre><xs:complexType name="auct.str.001.01" > <xs:sequence > <xs:element name="GnlInf" type="GeneralInformation" /> <xs:element name="Sts" type="Status" /> </xs:sequence> </xs:complexType></pre>
auct.str.001.01/GnlInf- General information (element)	
Description	General information
Type	<u>GeneralInformation</u>
Source	<pre><xs:element name="GnlInf" type="GeneralInformation" /></pre>
auct.str.001.01/Sts- Status (element)	
Description	Status
Type	<u>Status</u>
Source	<pre><xs:element name="Sts" type="Status" /></pre>