

## Structure of message: Coupons fixing report (otcc.cpn.001.01)

### Description:

The coupons fixing report presents all floating coupon payments for which a floating reference rate is fixed on the given date.

### Structure:

No.	Or	< XML Tag >	Name	Multiplicity	Type
0		<u>KDPWDocument</u>	KDPW system message	[1..1]	<u>KDPWDocument</u>
0.1		<u>otcc.cpn.001.01</u>	Coupons fixing report	[1..1]	<u>otcc.cpn.001.01</u>
1		<u>Pgntn</u>	Pagination	[1..1]	<u>Pagination</u>
1.1		<u>PgNb</u>	Page number	[1..1]	<u>Max5Int</u>
1.2		<u>LastPgInd</u>	Last page indicator	[1..1]	<u>YesNoIndicator</u>
2		<u>GnInf</u>	General information	[1..1]	<u>GeneralInformation</u>
2.1		<u>SndrMsgRef</u>	Sender message reference	[1..1]	<u>Max16Text</u>
2.2		<u>FuncOfMsg</u>	Function of message	[1..1]	<u>FunctionOfMessage</u>
2.3		<u>CreDtTm</u>	Creation date and time	[0..1]	<u>DateAndDateTimeChoice</u>
2.3.1	{ or	<u>Dt</u>	Date	[1..1]	<u>ISODate</u>
2.3.2	or }	<u>DtTm</u>	Date and time	[1..1]	<u>ISODateTime</u>
2.4		<u>StmntDtTm</u>	Statement date and time	[1..1]	<u>ISODate</u>
3		<u>StmntForAcct</u>	Statement for PA account	[0..n]	<u>StatementForAccount</u>
3.1		<u>PAAcct</u>	PA account identifier where transactions are registered	[1..1]	<u>Max35Text</u>
3.2		<u>Trad</u>	Trade	[0..n]	<u>TradeDetails</u>
3.2.1		<u>CCPTradId</u>	KDPW_CCP trade identifier	[1..1]	<u>Max16Text</u>
3.2.2		<u>CMDealId</u>	Confirmation platform deal identifier	[0..1]	<u>Max16Text</u>
3.2.3		<u>Ccy</u>	Currency	[1..1]	<u>CurrencyCode</u>
3.2.4		<u>Prdct</u>	Product	[1..1]	<u>Max16Text</u>
3.2.5		<u>CpnDtls</u>	Coupon details	[0..n]	<u>CouponDetails</u>
3.2.5.1		<u>CpnVal</u>	Coupon value	[1..1]	<u>SignedAmount</u>
3.2.5.2		<u>CpnPmtDt</u>	Coupon payment date	[1..1]	<u>ISODate</u>
3.2.5.3		<u>LegDef</u>	Leg definition	[1..1]	<u>Max16Text</u>
3.2.5.4		<u>Rate</u>	Coupon floating reference rate	[1..1]	<u>Rate</u>

## Message component elements:

<b>KDPWDocument- KDPW system message (element)</b>	
<b>Description</b>	KDPW system message
<b>Type</b>	<a href="#">KDPWDocument</a>
<b>Source</b>	<xs:element name="KDPWDocument" type="KDPWDocument" />
<b>Amount- Amount (simple type)</b>	
<b>Description</b>	Amount
<b>Type</b>	Derivative of type: xs:decimal
<b>Format</b>	Min. value=0 Number of decimal places=2 Number of characters=14
<b>Source</b>	<pre>&lt;xs:simpleType name="Amount" &gt;   &lt;xs:restriction base="xs:decimal" &gt;     &lt;xs:minInclusive value="0" /&gt;     &lt;xs:fractionDigits value="2" /&gt;     &lt;xs:totalDigits value="14" /&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>
<b>Code4Text- Qualifier (simple type)</b>	
<b>Description</b>	Qualifier, code
<b>Type</b>	Derivative of type: xs:string
<b>Format</b>	Min. length=4 Max. length=4
<b>Source</b>	<pre>&lt;xs:simpleType name="Code4Text" &gt;   &lt;xs:restriction base="xs:string" &gt;     &lt;xs:whiteSpace value="collapse" /&gt;     &lt;xs:minLength value="4" /&gt;     &lt;xs:maxLength value="4" /&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>
<b>CouponDetails- Coupon details (complex type)</b>	
<b>Description</b>	Coupon details
<b>Component elements</b>	<a href="#">CpnVal</a> <a href="#">CpnPmtDt</a> <a href="#">LegDef</a> <a href="#">Rate</a>
<b>Source</b>	<pre>&lt;xs:complexType name="CouponDetails" &gt;   &lt;xs:sequence &gt;     &lt;xs:element name="CpnVal" type="SignedAmount" /&gt;</pre>

	<pre> &lt;xs:element name="CpnPmtDt" type="ISODate" /&gt; &lt;xs:element name="LegDef" type="Max16Text" /&gt; &lt;xs:element name="Rate" type="Rate" /&gt; &lt;/xs:sequence&gt; &lt;/xs:complexType&gt; </pre>
<b>CouponDetails/CpnVal- Coupon value (element)</b>	
<b>Description</b>	Coupon value
<b>Type</b>	<u>SignedAmount</u>
<b>Source</b>	<pre>&lt;xs:element name="CpnVal" type="SignedAmount" /&gt;</pre>
<b>CouponDetails/CpnPmtDt- Coupon payment date (element)</b>	
<b>Description</b>	Coupon payment date
<b>Type</b>	<u>ISODate</u>
<b>Source</b>	<pre>&lt;xs:element name="CpnPmtDt" type="ISODate" /&gt;</pre>
<b>CouponDetails/LegDef- Leg definition (element)</b>	
<b>Description</b>	Leg definition
<b>Type</b>	<u>Max16Text</u>
<b>Source</b>	<pre>&lt;xs:element name="LegDef" type="Max16Text" /&gt;</pre>
<b>CouponDetails/Rate- Coupon floating reference rate (element)</b>	
<b>Description</b>	Coupon floating reference rate
<b>Type</b>	<u>Rate</u>
<b>Source</b>	<pre>&lt;xs:element name="Rate" type="Rate" /&gt;</pre>
<b>CurrencyCode- Currency code (simple type)</b>	
<b>Description</b>	Currency code
<b>Type</b>	Derivative of type: xs:string
<b>Format</b>	xs:pattern=[A-Z]{3,3}
<b>Source</b>	<pre> &lt;xs:simpleType name="CurrencyCode" &gt;   &lt;xs:restriction base="xs:string" &gt;     &lt;xs:pattern value="[A-Z]{3,3}" /&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>
<b>DateAndDateTimeChoice- Date and time (complex type)</b>	
<b>Description</b>	Date and time
<b>Component elements</b>	<u>Dt</u> <u>DtTm</u>
<b>Source</b>	<pre> &lt;xs:complexType name="DateAndDateTimeChoice" &gt;   &lt;xs:sequence &gt;     &lt;xs:choice &gt;       &lt;xs:element name="Dt" type="ISODate" /&gt;       &lt;xs:element name="DtTm" type="ISODateTime" /&gt;     &lt;/xs:choice&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt; </pre>

	<pre> &lt;/xs:choice&gt; &lt;/xs:sequence&gt; &lt;/xs:complexType&gt; </pre>				
<b>DateAndDateTimeChoice/Dt- Date (element)</b>					
<b>Description</b>	Date				
<b>Type</b>	<a href="#">ISODate</a>				
<b>Source</b>	<code>&lt;xs:element name="Dt" type="ISODate" /&gt;</code>				
<b>DateAndDateTimeChoice/DtTm- Date and time (element)</b>					
<b>Description</b>	Date and time				
<b>Type</b>	<a href="#">ISODateTime</a>				
<b>Source</b>	<code>&lt;xs:element name="DtTm" type="ISODateTime" /&gt;</code>				
<b>FunctionOfMessage- Function of message (simple type)</b>					
<b>Description</b>	Function of message				
<b>Type</b>	Derivative of type: xs:string				
<b>Format</b>	<table border="1"> <thead> <tr> <th>Code</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>NEWM</td> <td>New message</td> </tr> </tbody> </table>	Code	Description	NEWM	New message
Code	Description				
NEWM	New message				
<b>Source</b>	<pre> &lt;xs:simpleType name="FunctionOfMessage" &gt;   &lt;xs:restriction base="xs:string" &gt;     &lt;xs:enumeration value="NEWM" /&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>				
<b>GeneralInformation- General information (complex type)</b>					
<b>Description</b>	General information				
<b>Component elements</b>	<a href="#">SndrMsgRef</a> <a href="#">FuncOfMsg</a> <a href="#">CreDtTm</a> {0,1} <a href="#">StmtDtTm</a>				
<b>Source</b>	<pre> &lt;xs:complexType name="GeneralInformation" &gt;   &lt;xs:sequence &gt;     &lt;xs:element name="SndrMsgRef" type="Max16Text" /&gt;     &lt;xs:element name="FuncOfMsg" type="FunctionOfMessage" /&gt;     &lt;xs:element name="CreDtTm" type="DateAndDateTimeChoice" minOccurs="0" /&gt;     &lt;xs:element name="StmtDtTm" type="ISODate" /&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt; </pre>				
<b>GeneralInformation/SndrMsgRef- Sender message reference (element)</b>					
<b>Description</b>	Sender message reference				
<b>Type</b>	<a href="#">Max16Text</a>				
<b>Source</b>	<code>&lt;xs:element name="SndrMsgRef" type="Max16Text" /&gt;</code>				
<b>GeneralInformation/FuncOfMsg- Function of message (element)</b>					

<b>Description</b>	Function of message									
<b>Type</b>	<a href="#">FunctionOfMessage</a>									
<b>Source</b>	<xs:element name="FuncOfMsg" type="FunctionOfMessage" />									
<b>GeneralInformation/CreDtTm- Creation date and time (element)</b>										
<b>Description</b>	Creation date and time									
<b>Type</b>	<a href="#">DateAndDateTimeChoice</a>									
<b>Source</b>	<xs:element name="CreDtTm" type="DateAndDateTimeChoice" minOccurs="0" />									
<b>GeneralInformation/StmDtTm- Statement date and time (element)</b>										
<b>Description</b>	Statement date and time									
<b>Type</b>	<a href="#">ISODate</a>									
<b>Source</b>	<xs:element name="StmDtTm" type="ISODate" />									
<b>ISODate- Date (simple type)</b>										
<b>Description</b>	Date									
<b>Type</b>	Derivative of type: xs:date									
<b>Format</b>										
<b>Source</b>	<xs:simpleType name="ISODate" > <xs:restriction base="xs:date" > </xs:restriction> </xs:simpleType>									
<b>ISODateTime- Date and time (simple type)</b>										
<b>Description</b>	Date and time									
<b>Type</b>	Derivative of type: xs:dateTime									
<b>Format</b>										
<b>Source</b>	<xs:simpleType name="ISODateTime" > <xs:restriction base="xs:dateTime" > </xs:restriction> </xs:simpleType>									
<b>KDPWDocument- KDPW system message (complex type)</b>										
<b>Description</b>	KDPW system message									
<b>Attributes</b>	<table border="0"> <thead> <tr> <th>Name</th> <th>Description</th> <th>Type</th> </tr> </thead> <tbody> <tr> <td>Sndr</td> <td>Sender</td> <td><a href="#">KDPWMemberIdentifier</a></td> </tr> <tr> <td>Rcvr</td> <td>Receiver</td> <td><a href="#">KDPWMemberIdentifier</a></td> </tr> </tbody> </table>	Name	Description	Type	Sndr	Sender	<a href="#">KDPWMemberIdentifier</a>	Rcvr	Receiver	<a href="#">KDPWMemberIdentifier</a>
Name	Description	Type								
Sndr	Sender	<a href="#">KDPWMemberIdentifier</a>								
Rcvr	Receiver	<a href="#">KDPWMemberIdentifier</a>								
<b>Component elements</b>	<a href="#">otcc.cpn.001.01</a>									
<b>Source</b>	<xs:complexType name="KDPWDocument" > <xs:sequence > <xs:element name="otcc.cpn.001.01" type="otcc.cpn.001.01" /> </xs:sequence> < xs:attribute name="Sndr" type="KDPWMemberIdentifier" use="required" />									

	<code>&lt; xs:attribute name="Rcvr" type="KDPWMemberIdentifier" use="required" /&gt; &lt;/xs:complexType&gt;</code>
<b>KDPWDocument/otcc.cpn.001.01- Coupons fixing report (element)</b>	
<b>Description</b>	Coupons fixing report
<b>Type</b>	<a href="#">otcc.cpn.001.01</a>
<b>Source</b>	<code>&lt;xs:element name="otcc.cpn.001.01" type="otcc.cpn.001.01" /&gt;</code>
<b>KDPWMemberIdentifier- KDPW member identifier (simple type)</b>	
<b>Description</b>	KDPW member identifier
<b>Type</b>	Derivative of type: xs:string
<b>Format</b>	Min. length=4 Max. length=4
<b>Source</b>	<code>&lt;xs:simpleType name="KDPWMemberIdentifier" &gt;   &lt;xs:restriction base="xs:string" &gt;     &lt;xs:whiteSpace value="collapse" /&gt;     &lt;xs:minLength value="4" /&gt;     &lt;xs:maxLength value="4" /&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</code>
<b>Max5Int- Integer (simple type)</b>	
<b>Description</b>	Integer, max. length 5 characters
<b>Type</b>	Derivative of type: xs:integer
<b>Format</b>	Number of characters=5 Min. value=0
<b>Source</b>	<code>&lt;xs:simpleType name="Max5Int" &gt;   &lt;xs:restriction base="xs:integer" &gt;     &lt;xs:totalDigits value="5" /&gt;     &lt;xs:minInclusive value="0" /&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</code>
<b>Max16Text- Text (simple type)</b>	
<b>Description</b>	Text, max. length 16 characters
<b>Type</b>	Derivative of type: xs:string
<b>Format</b>	Min. length=1 Max. length=16
<b>Source</b>	<code>&lt;xs:simpleType name="Max16Text" &gt;   &lt;xs:restriction base="xs:string" &gt;     &lt;xs:minLength value="1" /&gt;     &lt;xs:maxLength value="16" /&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</code>
<b>Max35Text- Text (simple type)</b>	

<b>Description</b>	Text, max. length 35 characters
<b>Type</b>	Derivative of type: xs:string
<b>Format</b>	Min. length=1 Max. length=35
<b>Source</b>	<pre>&lt;xs:simpleType name="Max35Text" &gt;   &lt;xs:restriction base="xs:string" &gt;     &lt;xs:minLength value="1" /&gt;     &lt;xs:maxLength value="35" /&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>
<b>Pagination- Pagination (complex type)</b>	
<b>Description</b>	Page number and last page indicator
<b>Component elements</b>	<a href="#">PgNb</a> <a href="#">LastPgInd</a>
<b>Source</b>	<pre>&lt;xs:complexType name="Pagination" &gt;   &lt;xs:sequence &gt;     &lt;xs:element name="PgNb" type="Max5Int" /&gt;     &lt;xs:element name="LastPgInd" type="YesNoIndicator" /&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt;</pre>
<b>Pagination/PgNb- Page number (element)</b>	
<b>Description</b>	Page number
<b>Type</b>	<a href="#">Max5Int</a>
<b>Source</b>	<pre>&lt;xs:element name="PgNb" type="Max5Int" /&gt;</pre>
<b>Pagination/LastPgInd- Last page indicator (element)</b>	
<b>Description</b>	Last page indicator
<b>Type</b>	<a href="#">YesNoIndicator</a>
<b>Source</b>	<pre>&lt;xs:element name="LastPgInd" type="YesNoIndicator" /&gt;</pre>
<b>Rate- Rate (simple type)</b>	
<b>Description</b>	Rate
<b>Type</b>	Derivative of type: xs:decimal
<b>Format</b>	Number of decimal places=12 Number of characters=14
<b>Source</b>	<pre>&lt;xs:simpleType name="Rate" &gt;   &lt;xs:restriction base="xs:decimal" &gt;     &lt;xs:fractionDigits value="12" /&gt;     &lt;xs:totalDigits value="14" /&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>
<b>SignedAmount- Amount (simple type)</b>	

<b>Description</b>	Amount
<b>Type</b>	Derivative of type: xs:decimal
<b>Format</b>	Max. value=1000000000000 Number of decimal places=12 Number of characters=24
<b>Source</b>	<pre>&lt;xs:simpleType name="SignedAmount" &gt;   &lt;xs:restriction base="xs:decimal" &gt;     &lt;xs:maxExclusive value="1000000000000" /&gt;     &lt;xs:fractionDigits value="12" /&gt;     &lt;xs:totalDigits value="24" /&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>
<b>StatementForAccount- Statement for PA account (complex type)</b>	
<b>Description</b>	Statement for PA account
<b>Component elements</b>	<a href="#">PAAcct</a> <a href="#">Trad</a> {0,unbounded}
<b>Source</b>	<pre>&lt;xs:complexType name="StatementForAccount" &gt;   &lt;xs:sequence &gt;     &lt;xs:element name="PAAcct" type="Max35Text" /&gt;     &lt;xs:element name="Trad" type="TradeDetails" minOccurs="0" maxOccurs="unbounded" /&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt;</pre>
<b>StatementForAccount/PAAcct- PA account identifier where transactions are registered (element)</b>	
<b>Description</b>	PA account identifier where transactions are registered
<b>Type</b>	<a href="#">Max35Text</a>
<b>Source</b>	<pre>&lt;xs:element name="PAAcct" type="Max35Text" /&gt;</pre>
<b>StatementForAccount/Trad- Trade (element)</b>	
<b>Description</b>	Trade
<b>Type</b>	<a href="#">TradeDetails</a>
<b>Source</b>	<pre>&lt;xs:element name="Trad" type="TradeDetails" minOccurs="0" maxOccurs="unbounded" /&gt;</pre>
<b>TradeDetails- Trade details (complex type)</b>	
<b>Description</b>	Trade details
<b>Component elements</b>	<a href="#">CCPTradId</a> <a href="#">CMDealId</a> {0,1} <a href="#">Ccy</a> <a href="#">Prdct</a> <a href="#">CpnDtIs</a> {0,unbounded}
<b>Source</b>	<pre>&lt;xs:complexType name="TradeDetails" &gt;   &lt;xs:sequence &gt;     &lt;xs:element name="CCPTradId" type="Max16Text" /&gt;</pre>



	<pre> &lt;xs:element name="CMDealId" type="Max16Text" minOccurs="0" /&gt; &lt;xs:element name="Ccy" type="CurrencyCode" /&gt; &lt;xs:element name="Prdct" type="Max16Text" /&gt; &lt;xs:element name="CpnDtls" type="CouponDetails" minOccurs="0" maxOccurs="unbounded" /&gt; &lt;/xs:sequence&gt; &lt;/xs:complexType&gt; </pre>
<b>TradeDetails/CCPTradId- KDPW_CCP trade identifier (element)</b>	
<b>Description</b>	KDPW_CCP trade identifier
<b>Type</b>	<a href="#">Max16Text</a>
<b>Source</b>	<pre>&lt;xs:element name="CCPTradId" type="Max16Text" /&gt;</pre>
<b>TradeDetails/CMDealId- Confirmation platform deal identifier (element)</b>	
<b>Description</b>	Confirmation platform deal identifier
<b>Type</b>	<a href="#">Max16Text</a>
<b>Source</b>	<pre>&lt;xs:element name="CMDealId" type="Max16Text" minOccurs="0" /&gt;</pre>
<b>TradeDetails/Ccy- Currency (element)</b>	
<b>Description</b>	Currency
<b>Type</b>	<a href="#">CurrencyCode</a>
<b>Source</b>	<pre>&lt;xs:element name="Ccy" type="CurrencyCode" /&gt;</pre>
<b>TradeDetails/Prdct- Product (element)</b>	
<b>Description</b>	Product
<b>Type</b>	<a href="#">Max16Text</a>
<b>Source</b>	<pre>&lt;xs:element name="Prdct" type="Max16Text" /&gt;</pre>
<b>TradeDetails/CpnDtls- Coupon details (element)</b>	
<b>Description</b>	Coupon details
<b>Type</b>	<a href="#">CouponDetails</a>
<b>Source</b>	<pre>&lt;xs:element name="CpnDtls" type="CouponDetails" minOccurs="0" maxOccurs="unbounded" /&gt;</pre>
<b>YesNoIndicator- Yes/No indicator (simple type)</b>	
<b>Description</b>	Yes/No indicator
<b>Type</b>	Derivative of type: xs:string
<b>Format</b>	<b>CodeDescription</b> Y True (yes) N False (no)
<b>Source</b>	<pre> &lt;xs:simpleType name="YesNoIndicator" &gt; &lt;xs:restriction base="xs:string" &gt; &lt;xs:enumeration value="Y" /&gt; &lt;xs:enumeration value="N" /&gt; </pre>

	<pre>&lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>
<b>otcc.cpn.001.01- Coupons fixing report (complex type)</b>	
<b>Description</b>	Coupons fixing report
<b>Component elements</b>	<u>Pgntn</u> <u>GnlInf</u> <u>StmtForAcct</u> {0,unbounded}
<b>Source</b>	<pre>&lt;xs:complexType name="otcc.cpn.001.01" &gt;   &lt;xs:sequence &gt;     &lt;xs:element name="Pgntn" type="Pagination" /&gt;     &lt;xs:element name="GnlInf" type="GeneralInformation" /&gt;     &lt;xs:element name="StmtForAcct" type="StatementForAccount" minOccurs="0" maxOccurs="unbounded" /&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt;</pre>
<b>otcc.cpn.001.01/Pgntn- Pagination (element)</b>	
<b>Description</b>	Page number and last page indicator
<b>Type</b>	<u>Pagination</u>
<b>Source</b>	<pre>&lt;xs:element name="Pgntn" type="Pagination" /&gt;</pre>
<b>otcc.cpn.001.01/GnlInf- General information (element)</b>	
<b>Description</b>	General information
<b>Type</b>	<u>GeneralInformation</u>
<b>Source</b>	<pre>&lt;xs:element name="GnlInf" type="GeneralInformation" /&gt;</pre>
<b>otcc.cpn.001.01/StmtForAcct- Statement for PA account (element)</b>	
<b>Description</b>	Statement for PA account
<b>Type</b>	<u>StatementForAccount</u>
<b>Source</b>	<pre>&lt;xs:element name="StmtForAcct" type="StatementForAccount" minOccurs="0" maxOccurs="unbounded" /&gt;</pre>